



#### CARTRIDGE REMOVAL PROCEDURE

1. REMOVE CLAMPS AND OPEN DOOR
2. REMOVE ALIGNMENT PIN FROM CARTRIDGE RACK
3. SLIDE OUT CARTRIDGE RACK
4. REMOVE DIRTY CARTRIDGES
5. INSERT CLEAN CARTRIDGES
6. SLIDE CARTRIDGE RACK BACK INTO HOUSING
7. INSERT ALIGNMENT PIN ON CARTRIDGE RACK
8. CLOSE DOOR AND SECURE CLAMPS



PALM HARBOR, FLORIDA

727 785 8500

TITLE : SQUARE BIN VENT CARTRIDGE REMOVAL

DRAWN	JDB	DATE	4/13/2012	DRAWING NO.
CHECKED	XXXX	SCALE	1:50	
				XXXX

THIS DRAWING & DESIGN IS THE PROPERTY OF J.D.B. DENSE FLOW INC, AND SHOULD NOT BE REPRODUCED, PUBLISHED, OR DISCLOSED TO OTHERS WITHOUT WRITTEN AUTHORIZATION FROM J.D.B. DENSE FLOW AND SHALL BE IN NO WAY USED AGAINST OR DETRIMENTAL TO J.D.B. DENSE FLOW INC.